Distributed by:

JAMECO® ELECTRONICS

www.Jameco.com ✦ 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

DataTwist® 5e UTP Cable

TIA/EIA-568-B.2, Category 5e Unbonded-Pair Cables

DATATWIST®

Jameco Part Number 234093 (1585A-877-1000)

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Standard Lengths		Standard Unit Wt.		Insulation Thickness		Nominal OD		Max. DCR (Ω/ 100m)	Max. DCR Unbal. (%)	Max. Cap. Unbal. (pF/ 100m)	Freq. (MHz)	Max. Atten. (dB/ 100m)	Min. PSUM NEXT (dB)	Min. PSUM ACR (dB/ 100m)	Min. PSUM ELFEXT (dB/ 100m)	Input Imped. (Ω)	Min. RL (dB)
				Ft.	m	Lbs.	kg	Inch	mm	Inch	mm										
24 AWG Solid Bare Copper • Twisted Pairs • Rip Cord • See Color Code Chart (below)																					
Plenum • FEP Teflon® Insulation • Flamarrest® Jacket (Available in Natural, Blue, Red, Orange, Yellow, Green, Gray, Black or Pink)																					
 Rip Cord	**1590A**	NEC: CMP CEC: CMP FT6	2	1000* 3000*	304.8 914.6	16.0 45.0	7.3 20.5	.007	.18	.175	4.44	9.38	5.0	330	1 10 16 31.25 62.5 100	2.0 6.5 8.2 11.7 17.0 22.0	62.3 47.3 44.3 39.9 35.5 32.3	60 41 36 28 19 11	60.8 40.8 36.7 30.9 24.8 20.8	100±15 100±15 100±15 100±15 100±15 100±15	20.0 25.0 25.0 23.6 21.5 20.1
*1000 ft. put-up available in Natural or Blue only. 3000 ft. put-up available in Natural only.																					
 Rip Cord	**1585A**	NEC: CMP CEC: CMP FT6	4	U-1000 1000 3000†	U-304.8 304.8 914.6	23.0 23.0 69.0	10.5 10.5 31.4	.007	.18	.200	5.08	9.38	3.0	330	1 4 10 16 31.25 62.5 100 200	2.0 4.1 6.5 8.2 11.7 17.0 22.0 32.0	62.3 53.3 47.3 44.3 39.9 35.4 32.3 27.8	60.0 49.0 41.0 36.0 28.0 19.0 11.0 1.0	60.8 48.7 40.8 36.7 30.9 24.8 20.8 14.7	100±15 100±15 100±15 100±15 100±15 100±15 100±15 100±25	20.0 23.0 25.0 25.0 23.6 21.5 20.1 15.0
†3000 ft. put-up available in Natural or Blue only. Jacket sequentially marked at 2 ft. intervals. Third party verified to TIA/EIA-568-B.2, Category 5e																					
Plenum • FEP Teflon Insulation • Fluorescent Pink Flamarrest Jacket																					
DataBrite®  Rip Cord	**1585B**	NEC: CMP CEC: CMP FT6	4	1000	304.8	24.0	10.9	.007	.18	.200	5.08	9.38	3.0	330	1 4 10 16 31.25 62.5 100 200	2.0 4.1 6.5 8.2 11.7 17.0 22.0 32.0	62.3 53.3 47.3 44.3 39.9 35.4 32.3 27.8	60.0 49.0 41.0 36.0 28.0 19.0 11.0 1.0	60.8 48.7 40.8 36.7 30.9 24.8 20.8 14.7	100±15 100±15 100±15 100±15 100±15 100±15 100±15 100±25	20.0 23.0 25.0 25.0 23.6 21.5 20.1 15.0
Jacket sequentially marked at 2 ft. intervals. Third party verified to TIA/EIA-568-B.2, Category 5e																					
Plenum • FEP Teflon Insulation • FEP Jacket (Available in Blue or White)																					
	**1585LC**** new	NEC: Limited Combustible FHC 25/50 CMP CEC: CMP FT6	4	U-1000 1000	U-304.8 304.8	23.0 23.0	10.5 10.5	.007	.18	.184	4.67	9.38	3.0	330	1 4 10 16 31.25 62.5 100 200	2.0 4.1 6.5 8.2 11.7 17.0 22.0 32.0	62.3 53.3 47.3 44.3 39.9 35.4 32.3 27.8	60.0 49.0 41.0 36.0 28.0 19.0 11.0 1.0	60.8 48.7 40.8 36.7 30.9 24.8 20.8 14.7	100±15 100±15 100±15 100±15 100±15 100±15 100±15 100±25	20.0 23.0 25.0 25.0 23.6 21.5 20.1 15.0
**1585LC does not have a rip cord. Jacket sequentially marked at 2 ft. intervals. Third party verified to TIA/EIA-568-B.2, Category 5e																					

ACR = Attenuation Crosstalk Ratio • DCR = DC Resistance • ELFEXT = Equal Level Far-end Crosstalk • NEXT = Near-end Crosstalk • PSUM = Power Sum • RL = Return Loss • UTP = Unshielded Twisted Pair(s)

Color Codes: DataTwist 5e

Pair No.	Color Combination
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown

Teflon is a DuPont trademark.